

WX Series

Wall speakers

The WX series are powerful 2-way performance speakers suited for a wide variety of applications, ensuring true-to-nature, high fidelity reproduction of music and speech. The elegant shaped synthetic enclosure is available in three different colours (black, white and Silver), making it blend into any environment, going from standard indoor home to special indoor design interiors. The included mounting bracket allows horizontal and vertical mounting as well as focussing of the speaker, and the 100V line transformer contains three steps of impedance for 100V applications or 8 Ω for standard low impedance applications. They are fitted with a protection network against tweeter overload.

WX302

The WX302 is the smallest speaker of the WX family, fitted with an 1" dome tweeter and a 3" low frequency loudspeaker. It delivers a power of 30W in standard 8 Ohm systems, but can also be used in 100V PA systems. The 100V line transformer has tapings for 20W, 10W and 5W. This speaker is available in three colours: white, black and Silver.

Horizontal Coverage: 100°
Vertical Coverage: 100°

100 VOLT **8 OHM**



WX502

The WX502 is the medium speaker of the WX family, fitted with an 1" dome tweeter and a 5 1/4" low frequency loudspeaker. It delivers a power of 50W in standard 8 Ohm systems, but can also be used in 100V PA systems. The 100V line transformer has tapings for 40W, 20W and 10W. This speaker is available in three colours: white, black and Silver.

Horizontal Coverage: 110°
Vertical Coverage: 110°

100 VOLT **8 OHM**



Technical Highlights

	Max Power	RMS Power	Max SPL	Sensitivity 1W / 1m	Power Taps – Impedance	Frequency Response ±3 dB	Frequency Range -10 dB	Dimensions (W x H x D)	Weight
WX302	60 Watt	30 Watt	100 dB	85 dB	20 / 10 / 5 Watt – 8 Ω	90Hz – 18kHz	60Hz – 20kHz	199x129x120 mm	1.66 Kg
WX502	100 Watt	50 Watt	102 dB	87 dB	40 / 20 / 10 Watt – 8 Ω	70Hz – 18kHz	55Hz – 20kHz	212x147x136 mm	2.54 Kg