


**POWERMATE
600-3**

**POWERMATE
1000-3**

**POWERMATE
1600-3**

**POWERMATE
2200-3**
MAX OUTPUT POWER (IHF-A) @40HM

2 x 1250 W

CHANNELS (Mono + Stereo)

4 + 4

6 + 4

12 + 4

18 + 4

MIC CHANNELS

6

10

16

22

AUX SEND / MONITOR / FX SENDS

1 / 1 / 1

2 / 2 / 2

DIGITAL AUDIO INTERFACE

4 x 4 USB 2.0, 96 kHz

MASTER EQ

9-band

11-band

EFFECTS

EFFECTS PRESETS / REMOTE CONTROL


100 factory + 20 user / Footswitch + MIDI

 ECHO / REVERB / HALLS, PLATE / ECHO /
DELAY / FANGER / CHORUS / DOUBLING

**SPEAKER PROTECTION ADJUSTABLE
RMS LIMITER** (against speaker thermal overload)

WEIGHT [LBS]

12,8



20,9



26,5



32,0


DIMENSIONS (WXHXD)

16.4" x 4.3" x 13.7"

20.1" x 6.1" x 19.6"

26.1" x 6.1" x 19.6"

32.2" x 6.1" x 19.6"

ACCESSORIES

GOOSENECK LAMP 4-POL

LitteLite

LitteLite

LitteLite

LitteLite

FS 11 FOOT SWITCH

FS 11

FS 11

FS 11

FS 11