



KRAMER

VP-444

12-Input HDMI & Analog ProScale™
Presentation Digital Scaler/Switcher with
Microphone Inputs & Ethernet Control

| VGA/UXGA - 15-pin HD | HDMI | Microphone -
3.5/6.5mm | Ethernet - RJ-45 | HDCP Compliant



The VP-444 is a high-performance presentation scaler/switcher for HDMI and computer graphics signals. The unit scales the video, embeds the audio, and outputs the signal to two HDMI (with embedded audio) outputs (with S/PDIF and balanced stereo audio) simultaneously

FEATURES

Kramer's PixPerfect™ Scaling Technology - Kramer's precision pixel mapping and high-quality scaling technology. High-quality 3:2 and 2:2 pull down de-interlacing and full up and down scaling of all video input signals

HDTV Compatible

HDCP Compliant

Video Inputs - 10 HDMI & 2 computer graphics video on 15-pin HD connectors

Scaled Outputs - 2 HDMI

22 Output Resolutions - Up to WUXGA/1080p

2 Microphone Inputs - For mixing, switching or talk-over (with 48V phantom selection)

Auto Input Scanning and Switching

Companion AFV (Audio-Follow-Video) - Stereo audio for every input (on terminal blocks)

Audio Inputs - 12 unbalanced stereo on terminal blocks & embedded audio for HDMI inputs, each with individual level controls

Audio Outputs - 1 S/PDIF on an RCA connector, 1 balanced stereo audio on a terminal block, embedded audio on the HDMI outputs

Multiple Aspect Ratio Selections - Full, overscan, underscan, letterbox & panscan

Audio DSP - Powerful digital audio signal processing, including audio equalization, mixing, delay, etc

Built-in ProcAmp - Color, hue, sharpness, noise, contrast & brightness

Color Sampling - Supports 4:4:4 (RGB and YUV) as well as 4:4:2 (YUV) color sampling

Constant Output Sync - No disruption on the output while switching between inputs and when no video is detected

Front Panel Control - Audio mute & freeze frame

Built-in Web Pages

Front Panel Lockout

Non-Volatile Memory - Saves final settings

Flexible Control Options - Front panel, IR remote with OSD (on-screen display), Ethernet with built-in Web pages & RS-232

Worldwide Power Supply - 100-240V AC



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|--|
| INPUTS: | 10 HDMI connectors (HDMI, HDCP version 1.4); 2 VGA on a 15-pin HD connector; 1 unbalanced stereo audio on 12 3-pin terminal block connectors; 2 mic on 6mm jack connectors (with selectable 48V phantom power) |
| OUTPUTS: | 2 HDMI connectors (HDMI, HDCP version 1.4); 1 S/PDIF on an RCA connector; 1 unbalanced stereo audio on a 5-pin terminal block connector |
| BANDWIDTH: | Up to 1080p, UXGA |
| SWITCHING TIME BETWEEN INPUTS: | 2 to 3 seconds |
| VIDEO LATENCY: | Less than 2 frames |
| OUTPUT RESOLUTIONS: | Native, 640x480 @60Hz, 800x600 @60Hz, 1024x768 @60Hz, 1280x768 @60Hz, 1360x768 @60Hz, 1280x720 @60Hz, 1280x800 @60Hz, 1280x1024 @60Hz, 1440x900 @60Hz, 1400x1050 @60Hz, 1680x1050 @60Hz, 1600x1200 @60Hz, 1920x1080 @60Hz, 1920x1200 @60Hz, 480p @60Hz, 720p @60Hz, 1080i @60Hz, 1080p @60Hz, 576p @50Hz, 720p @50Hz, 1080i @50Hz, 1080p @50Hz |
| CONTROLS: | HDMI 1 to HDMI 10 and PC 1 to PC 2 input selector buttons, Freeze, Mute buttons, Menu and navigation buttons, Reset to XGA/720p and lock buttons, RS-232, IR, Ethernet (OSD and Web pages), USB for firmware upgrading |
| POWER CONSUMPTION: | 100-240V AC, 22VA max |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| INCLUDED ACCESSORIES: | Power cord, rack ears, IR remote control |
| Product Dimensions | 19" x 7.20 x 1U (43.6cm x 18.30cm x 4.36cm) W, D, H |
| Product Weight | 1.8kg (4.0lbs) approx |
| Shipping Dimensions | 55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H |
| Shipping Weight | 2.5kg (5.5lbs) approx |



