



## NC3MXCC

3 pole male cable connector, RF-protected, gold contacts

Cable O.D.: 5.4 - 6.2 mm

Crimp Size Shield: 6.5 mm (hex)

The XCC XLR cable connector Series with circumferential shield contact provides excellent RF-protection to transmit digital audio signals most efficient and reliable. This XLR features a coaxial ground spring and a coaxial hex crimp ferrule at the cable entrance for proper and reliable transition of the shield to the shell.

### Features & Benefits

- 3 pole cable connector with a circumferential shield contact for best EMI protection
- Rugged zinc diecast shell, long lasting and durable
- Boot with rubber gland gives high protection against bending stresses
- XCCR coding ring to indicate digital AES signals included
- Chuck type strain relief system for secure clamping of cables

**Technical Information**

Product	
<b>Title</b>	NC3MXCC
<b>Connection Type</b>	XLR
<b>Gender</b>	male

Electrical	
<b>Capacitance between contacts</b>	$\leq 4$ pF
<b>Contact resistance</b>	$\leq 3$ m $\Omega$
<b>Dielectric strength</b>	1,5 kVdc
<b>Insulation resistance</b>	$> 10$ G $\Omega$ (initial)
<b>Rated current per contact</b>	16 A
<b>Rated voltage</b>	$< 50$ V
<b>Shielding effectiveness</b>	$> 55$ dB @ 1.3 GHz

Mechanical	
<b>Cable O.D.</b>	5.4 - 6.2 mm
<b>Crimp size</b>	6,47 Hex crimp (shield) acc. IEC 60803 (die designation E)
<b>Insertion force</b>	$\leq 20$ N
<b>Withdrawal force</b>	$\leq 20$ N
<b>Lifetime</b>	$> 1000$ mating cycles
<b>Wiresize</b>	max. 2.5 mm <sup>2</sup>
<b>Wiresize</b>	max. 14 AWG
<b>Wiring</b>	Solder contacts
<b>Locking device</b>	Latch lock

Material	
<b>Boot</b>	Polyurethan
<b>Coding Ring</b>	PA 6 15% GR
<b>Contact plating</b>	0.2 µm Au hard alloy over 2 µm Ni
<b>Contacts</b>	Brass (CuZn39Pb3)
<b>Crimp ferrule</b>	CuZn39Pb3, Ni plated
<b>Insert</b>	Polyamide (PA66)
<b>Locking element</b>	Zinc diecast (ZnAl4Cu1)
<b>Shell</b>	Zinc diecast (ZnAl4Cu1)
<b>Shell plating</b>	Nickel
<b>Strain relief</b>	Polyacetal (POM)
<b>Circumferential ground spring</b>	CuSn6, Ni plated

Environmental	
<b>Approvals</b>	UL
<b>Flammability</b>	UL 94 V-0
<b>Standard compliance</b>	IEC 61076-2-103
<b>Protection class</b>	IP 40
<b>Solderability</b>	Complies with IEC 68-2-20
<b>Temperature range</b>	-30 °C to +80 °C