



Start
Elektronik San. ve Tic. Ltd. Şti.

AVLON LED EKRAN

BIG SIZE MAGIC INDOOR P2.6 / P2.9 / 3.9 OUTDOOR P3.9 / P4.8 / P5.9



Genel Özellikleri

- Hızlı ve Kolay Kurulum
- Ön (OPT) / Arka Teknik Müdahale
- Kolay ve Güçlü Kilit Sistemi
- Merdiven Görevi Gören Kulplar
- 500x1000 Ölçüsüyle Hafif ve Kolay Taşınabilir Kabin
- 5-10-15 Derece İç ve Dış Curve Özelliği (OPT)
- Fansız Pasif Soğutma
- Power Control Box Sök-Tak Ergonomik Tasarım
- 500x500 Acrux Kabin ile Uyumlu Sistem
- Smart LCD ile Kabin Sıcaklığının ve Voltajın Görüntülenmesi (OPT)
- Çalışma Saatini Hafızaya Kaydetme Özelliği (OPT)
- Rental, Fixed, Indoor ve Outdoor



ULTRA
BRIGHT



HIGH
VIEWING ANGLE



OUTDOOR



HIGH
REFRESH RATE



FANLESS
DESIGN



IP 65



SLIM
DESIGN



EASY
MAINTENANCE



MOBILE SYSTEM
COMPATIBLE



NO GHOST
(CLEAN IMAGE)



ENERGY
SAVING



24/7
USAGE



EASY
INSTALLATION



INDOOR



IP 54



11 KG



CURVED



FRONT
SOLUTION

Teknik Özellikler	INDOOR			OUTDOOR		
Pixel	P2.6	P2.9	P3.9	P3.9	P4.8	P5.9
Led Type	SMD2020	SMD2020	SMD2020	SMD1921	SMD1921	SMD2525
Brightness	1100nits/m2	1100nits/m2	1200nits/m2	5500nits/m2	5500nits/m2	5500nits/m2
Refresh Rate	3840Hz	1920Hz	1920Hz	1920Hz	1920Hz	1920Hz
Driving Method	1/24	1/23	1/16	1/16	1/13	1/8
Module Size	250x250	250x250	250x250	250x250	250x250	250x250
Module Resolution	100X100	84X84	64x64	64X64	52X52	42X42
Cabinet Size	500x1000	500x1000	500x1000	500x1000	500x1000	500x1000
Pixel Density	147456	112896	65536	65536	43264	28224
Max. Power	460	440	425	520	525	550
Avg. Power	250	240	225	275	280	300
IC Driver	ICN2050 / MBI5153	ICN2038 / MBI5124	ICN2038 / MBI5124	ICN2038 / MBI5124	ICN2038 / MBI5124	ICN2038 / MBI5124
Power Supply	VAT 5V60A	VAT 5V60A	VAT 5V60A	VAT 5V60A	VAT 5V60A	VAT 5V60A
Module Per Cabinet	4	4	4	2	2	2
Weight Cabinet	11 Kg	11 Kg	11 Kg	11 Kg	11 Kg	11 Kg
Colors	281 Trillion	281 Trillion	281 Trillion	281 Trillion	281 Trillion	281 Trillion
Min. Viewing Distance	2,5 mt	3 mt	4 mt	4 mt	5 mt	6 mt
Horizontal Viewing Angle	140	140	140	140	140	140
Vertical Viewing Angle	140	140	140	140	140	140
Led Lifetime	100.000 hours	100.000 hours	100.000 hours	100.000 hours	100.000 hours	100.000 hours
Input Voltage	110-240V	110-240V	110-240V	110-240V	110-240V	110-240V
Operation Temperature	--40+ 70 C	--40+ 70 C	--40+ 70 C	--40+ 70 C	--40+ 70 C	--40+ 70 C
Ingress Protection	IP54	IP54	IP54	IP65	IP65	IP65
Gray Level	65536	65536	65536	65536	65536	65536



Start
Elektronik San. ve Tic. Ltd. Şti.

Şafak Mahallesi Karanfil Caddesi 854. Sokak 8/A 06830 Gölbaşı / ANKARA Tel: 0312 485 60 00 - 0312 446 96 66